

## *Service Additives – Engine Oil*

Version: SA3/02

## **Valvoline™ Engine Oil Stop Leak**

**Special additive package to help reducing oil consumption by conditioning of engine seals to maintain operation reliability.**

### **Applications**

Suitable for all petrol and diesel engines with all commonly used motor oils.

Apply when

- Oil consumption and loss through sweating gaskets is diagnosed.

### **Operating instructions**

Add Valvoline Engine Oil Stop Leak to the engine oil and let the engine idle for 10 minutes to ensure adequate mixing.

Important note:

Do NOT exceed maximum crankcase capacity

Dosage:

Suitable for 5 liters of engine oil.

Harmless to the engine up to a maximum concentration of 10% of engine oil.

Add content of the metal bottle (300 ml) to at least 3 liters of engine oil.

Check oil system for leakage.

If leakage persists after approximately 3 days then seals are likely to be damaged and should be replaced.

### **Features & Benefits**

#### **Direct effect**

Valvoline Engine Oil Stop Leak has a direct effect after application.

#### **Positive environmental effect**

Prevents pollution of the environment due to uncontrolled loss of engine oil.

#### **Easy to use**

Application through simply adding it to the engine oil. No specialist tools or equipment required.

#### **Universal application**

Valvoline Engine Oil Stop Leak is suitable for petrol and diesel engines and all commonly used motor oils and engine seals.

# PRODUCT INFORMATION



## Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit [www.valvolineeurope.com](http://www.valvolineeurope.com)

## Typical properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

Engine Oil Stop Leak	
Appearance	Light yellow
Specific Gravity @ 20°C	0,87
Flash Point, °C	> 200

**This information only applies to products manufactured in the following location(s): Europe**

## Health & Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet <http://msds.valvoline.com>

## Protect the environment

Take used chemical to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

## Storage

We recommend to store all packages under cover. Keep container tightly closed and stored in a cool, dry and well ventilated place. Products should be stored inside and do not exposed to direct sunlight and high temperatures. Avoid freezing conditions.

Replaces – SA3/01

™ Trademark of Valvoline, registered in various countries © 2017

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ellis Enterprises B.V. and its affiliates assume legal responsibility.